

# DIGITUS Защита обжимных соединений

## AL-SK3 EAN 4016032007364





#### Fiber Optic Crimp Splice Protection 1 Tray with 12pcs.

Накладная защита стыка оптического волокна

Размеры: 1.2x3.2x30 мм

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	2.50	30.00	30.00	10.00	9,000.00
Packaging Unit Inside	10	0.13	10.00	5.00	3.50	175.00
Packaging Unit Single	1	0.01	9.50	4.50	0.40	17.10
Net single without Packaging	1	0.01	0.00	0.00	0.00	0.00

### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- · eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect
  against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal
  quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum
  operating temperature of the cable
- · Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com