

DIGITUS Hirose Modular Plug, CAT 6 TM 21

A-MO6 8/8 HRS
EAN 4016032132943



Hirose Modular Plug, CAT 6 TM21 8P8C, shielded, for round cable, incl. hood

Estas fichas modulares podem ser usadas para estabelecer ligações rápidas e simples.

- Características gerais:

- Ciclos de emparelhamento: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Material estrutura do conector: Policarbonato, perfurado
- Diâmetro condutor de cobre: AWG (27/7 ... 24/7)
- Capacidade actual de carga: 1A a 50°C
- Diâmetro da tomada exterior: 5,5 ... 6,2mm

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	0.01	3.00	1.50	11.00	49.50
Packaging Unit Inside	1	0.01	3.00	1.50	11.00	49.50
Packaging Unit Single	1	0.01	3.00	1.50	11.00	49.50
Net single without Packaging	1	0.01	3.00	1.50	11.00	13.00

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com