

# **DIGITUS Levelling feet for network and server cabinets**

DN-19 FEET EAN 4016032193623





## Levelling feet for network- and server cabinets adjustable height, 4 pieces

The Levelling Feet are delivered in a set of 4 pieces inclusive mounting material and are therefore quick and easy to install and to use. With a loading capacity of 250 kg per unit they provide a high stability for your 482.6 mm (19") cabinets. Suitable for all free standing cabinets of Unique- and Dynamic Basic series as well as standard wall mounting cabinets of the Unique series.

- · Mounting under the cabinets
- Set = 4 pcs.
- Foot: PVC
- Load capacity per foot: 250 kg
- M10

### Package contents

- 4 x Levelling feet
- 4 x Nut

| Logistics                    |                 |                |               |               |                |          |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|----------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³      |
| Packaging Unit Carton        | 30              | 2.10           | 38.50         | 22.00         | 8.00           | 6,776.00 |
| Packaging Unit Inside        | 1               | 0.07           | 18.00         | 5.50          | 4.50           | 445.50   |
| Packaging Unit Single        | 1               | 0.07           | 18.00         | 5.50          | 4.50           | 445.50   |
| Net single without Packaging | 1               | 0.07           | 18.00         | 5.50          | 4.50           | 445.50   |

#### More images:











#### Safety notes

• When installing and using the accessory product for network cabinets, observe the respective safety instructions of the manufacturer or the cabinet system in which you want to use the accessory.

#### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com