

DIGITUS CAT 5e SF/UTP патч-кабель

DK-1532-005
EAN 4016032198703



CAT 5e SF-UTP patch cord, PVC AWG 26/7, length 0.5 m, color grey

The DIGITUS® Category 5e Class D patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 5e specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS® Category 5e cabling. The performance is tested up to 100 MHz inclusive performance characteristics such as near end cross talk ("NEXT"). DIGITUS® patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume. Each cable is fitted with a molded boot which comes with kink protection and strain relief. Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking. You can easily identify the Category 5e, because of the transparent blue colored connector.

Отличная производительность и качество связи для Вашей сети.

- 2 разъема RJ45 (8P8C)
- Колпачки с защитой от излома, натяжения и перегиба
- Метки длины на оболочке
- Assortment: Twisted Pair Patch Cables
- Configuration: 1:1
- Connector 1: Modular RJ45 (8/8) plug
- Connector 2: Modular RJ45 (8/8) plug
- Packaging: DIGITUS Polybag
- Category: CAT 5e
- Shielding: SF-UTP, foil and braid shielding
- Length: 0.5 m
- Color: grey
- Jacket: PVC
- Slim Version: no
- Structure: 4 x 2 AWG 26/7, twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	250	7.00	36.00	36.00	27.00	34,992.00
Packaging Unit Inside	10	0.28	5.50	22.00	26.00	3,146.00
Packaging Unit Single	1	0.03	1.10	11.50	21.00	265.65
Net single without Packaging	1	0.02	50.00	1.20	1.30	0.00