

# DIGITUS CAT 6, modular couplers, shielded

**AT-AG 8/8 C6S**  
**EAN 4016032229032**



**Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing**

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Technical properties:
- Housing material: ABS UL-94V-0
- Contacts coating: Nickel, gold-plated 0.5 μ

- Shielding: Tinned bronze
- PCB:FR4, UL 94V-0
- Material contacts: Phosphor bronze
- Physical properties:
- Mating cycles: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)
- Insertion force: 30N max. (IEC 60603-7-5)
- Retention strength: 7.7 kg between jack and plug

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1000	11.67	30.00	55.00	27.00	44,550.00
Packaging Unit Inside	100	1.17	14.00	25.50	10.50	3,748.50
Packaging Unit Single	1	0.01	8.00	10.00	1.80	144.00
Net single without Packaging	1	0.09	1.60	3.00	1.80	0.00