

DIGITUS CAT 6, модульный переходник, экранированный

AT-AG 8/8 C6S
 EAN 4016032229032



Modular Coupling, 8P8C, 1:1 shielded CAT6, metal housing

The modular CAT 6 coupler from DIGITUS® consists of two shielded RJ45 sockets. The assignment is "1:1".

- Покрытие контактов: никель, позолота 0,5μ

- PCB:FR4, UL 94V-0
- 12 x, 35° угловые, вертикальное подключение
- Физическое описание
- Циклов стыка: ≥ 750 (ISO/IEC 11801, IEC 60603-7-5)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1000	11.67	30.00	55.00	27.00	44,550.00
Packaging Unit Inside	100	1.17	14.00	25.50	10.50	3,748.50
Packaging Unit Single	1	0.01	8.00	10.00	1.80	144.00
Net single without Packaging	1	0.09	1.60	3.00	1.80	0.00

Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com