

# DIGITUS Roof Ventilation Unit for 483 mm (19") Wall Mounting Cabinets

**DN-19 FAN-2-WM-T-SW**  
**EAN 4016032250586**



**Roof vent. unit, wall mounting cabinets 2 fans, thermostat, switch, black (RAL 9005)**

The Roof Ventilation Units are suitable for all mounted wall mounting cabinets of the Unique series as well as for all unmounted network- and server cabinets (-EC). The installation in the roof module of the cabinet can be done quick and easy. A switch as well as an adjustable thermostat provide best options for customizations. The model is available in standard color grey (RAL 7035) and black (RAL 9005), equipped with two fans.

**The DIGITUS 483 mm (19") equipment is made for high demand IT-infrastructure solutions, produced on German standards.**

- Housing made out of sturdy steel sheet
- Fans with grid covers
- 2 fans
- incl. thermostat, adjustable from 0 °C up to +70 °C

- On/off switch
- Air flow: 4.6 m³/min.
- 1.8 m cable with CEE 7/7 (Type-F) plug
- 1.8 m cable with CEE 7/7 (Type F) plug

**Attributes**

- Color: black, RAL 9005
- Air flow: 4.6 m3/min
- Filter: no
- For cabinet series: Wall Mounting
- Inch form factor (IEC 60297): 482.6 mm (19")
- Mounting area: Roof
- Quantity of mounted fans: 2

**Package contents**

- Fixing material

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	15	27.90	59.50	50.00	51.50	153,212.00
Packaging Unit Inside	1	1.86	22.00	38.50	9.00	7,623.00
Packaging Unit Single	1	1.86	22.00	38.50	9.00	7,623.00
Net single without Packaging	1	1.83	0.00	0.00	0.00	0.00

**More images:**



**Safety notes**

- When installing and using the accessory product for network cabinets, observe the respective safety instructions of the manufacturer or the cabinet system in which you want to use the accessory.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)