


DIGITUS DIGITUS цветные монтажные шнуры, LC OM3 50/125 μ, одиночные

DK-25332-02/3
EAN 4016032263005



FO pigtail set, 12 pcs., LC, MM OM3 50/125 μ loose buffer, color code DIN IEC 304, 2 m

The DIGITUS® Fiber Optic Colored Pigtails are available as LC Simplex, SC Simplex and ST Simplex version and offer with the classes OS2, OM2, OM3 and OM4 best performance and link quality for your network. The connector conforms acc. IEC 61754-4 2002 and is equipped with a Zirconia ceramic ferrule. The colored buffers are color coded according to IEC 304 (white, violet, turquoise, black, red, pink, orange, gray, green, yellow, brown, blue).

Отличная производительность и качество связи для Вашей сети.

- LC одиночный монтажный шнур, OM3 50/125 μ 2 м
- Стандартный разъем согл. IEC 61754-4 2002
- Рабочая температура: -25°C ... +80°C
- Температура хранения: -20°C ... +65°C
- Вносимые потери MM ПК: макс. 0,4 дБ

- Обратное затухание MM ПК: > 25 дБ
- Втулка из циркониевой керамики
- Диаметр сердцевины: Ш 0,9 ± 0,1 мм
- Основная оболочка: акрил; Ш 250± 15μm
- Окрашенный буфер, согласно IEC 304, цвета - белый, фиолетовый, бирюзовый, чёрный, красный, розовый, жёлтый, коричневый, синий
- 12 шт. в упаковке
- свободный буфер
- Boot: single-color
- Cable jacket: LSOH
- Connector 1: LC
- Fiber class: OM3
- Fiber diameter: 50/125μ
- Mode: Multimode
- Length: 2 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	160	8.33	41.00	41.00	28.00	47,068.00
Packaging Unit Inside	20	1.04	19.00	19.00	12.00	4,332.00
Packaging Unit Single	1	0.05	17.00	17.00	1.00	289.00
Net single without Packaging	1	0.05	15.00	15.00	1.00	0.00