

DIGITUS DIGITUS крепёжный набор для 483 мм (19") КОМПОНЕНТОВ

DN-70101-1
EAN 4016032271192



Wireless LAN antenna base, magnet mount RP-SMA connector, 1.5m low loss cable

Wireless LAN antenna base, magnet mount,RP-SMA connector, 1.5m low loss cable

Увеличивает дальность и зону покрытия беспроводной сети, улучшает качество сигнала

- Подходит для беспроводных сетей диапазона 2,4 ГГц - для всех беспроводных сетевых изделий DIGITUS ®
- RP-SMA разъёмы
- Металлическое основание с сильным магнитом
- Длина кабеля 1,50 м
- Кабель с низкими потерями

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	100	15.50	54.50	45.00	28.00	68,670.00
Packaging Unit Inside	1	0.16	4.80	11.00	18.00	950.40
Packaging Unit Single	1	0.16	4.80	11.00	18.00	950.40
Net single without Packaging	1	0.11	5.00	4.00	4.00	80.00

More images:



Safety notes

- The performance of the antenna depends heavily on the location. Ensure that the antenna is installed in a location that allows optimum signal distribution, without obstacles such as thick walls or metal objects.
- To avoid sources of interference, antennas should not be installed near electrical devices such as microwaves, radios or other strong sources of interference, as these can affect the signal.
- Avoid direct contact with salty air or other corrosive environments that could damage the antenna or connections.
- Check the antenna regularly for damage, loose connections or dirt. Dust or dirt on the antenna or the connections can significantly impair the signal quality.

- Make sure that the frequency of the antenna matches your network adapter or router.
- Ensure that the antenna in conjunction with the network adapter or router complies with local standards and approvals.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com