

# DIGITUS Соединительный кабель USB 2.0

AK-300100-010-S  
EAN 4016032282549



**USB connection cable, type A M/M, 1.0m, USB 2.0 compatible, bl**

Для подключения внешних USB-устройств (с разъёмом типа A) к USB-хосту (например, ПК, ноутбука или USB-разветвителя).  
Скорость передачи до 480 Мбит/с (High-Speed).

**Обеспечивает надежное и быстрое подключение внешних USB устройств к ПК при низкой чувствительности к электромагнитным помехам.**

**Attributes**

- Assortment: USB Cables
- Color cable: black
- Color connector: black
- Connector 1: USB A, plug
- Connector 2: USB A, plug
- Connector surface: nickel-plated
- Hoods: molded
- USB compliance: USB 2.0
- Length: 1 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	14.00	32.00	45.00	25.00	36,000.00
Packaging Unit Inside	10	0.28	22.00	19.00	4.00	1,672.00
Packaging Unit Single	1	0.03	0.70	9.20	19.60	126.22
Net single without Packaging	1	0.02	0.80	10.00	8.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)