

# DIGITUS Cabo de ligação DisplayPort

**AK-340100-030-S**  
**EAN 4016032288961**



**DisplayPort connection cable, DP M/M, 3.0m, w/interlock, Ultra HD 4K, bl**

Este cabo HD áudio/vídeo digital de elevado desempenho serve para a ligação de computadores ou computadores portáteis a monitores com interface DisplayPort.

**Ideal para CAD/CAM, GIS, desenvolvimento 3D, simulação em tempo real e mais.**

- Suporta até 4K/2K com 60Hz
- Suporta uma resolução de vídeo até 4K (3840x2160)@60Hz, Full HD (1920x1080)@120Hz
- Assortment: DisplayPort Cables
- AWG: 30
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.2
- Ferrite filter: none
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CCS
- Length: 3 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	50	8.30	44.00	31.00	22.00	30,008.00
Packaging Unit Inside	5	0.83	16.00	11.00	16.00	2,816.00
Packaging Unit Single	1	0.17	16.00	2.50	15.00	600.00
Net single without Packaging	1	0.12	13.50	13.00	3.00	0.00

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)