

DIGITUS CAT 6A modular couplers, shielded

DN-93905
 EAN 4016032291824



CAT6A modular coupler, full shielded RJ45 to RJ45

Coincide com os requisitos de desempenho de canal, Classe EA ISO/IEC 11801 para até 550MHz

- 2 x RJ-45 fêmea
- Tarefa 1:1
- Versão revestida

- Material da caixa de protecção: Folha de latão - niquelado brilhante
- Material PCB: FR4, espessura 1,2mm
- Material dos contactos: Bronze fósforo
- Revestimento dos contactos: Níquel, dourado 0,6µ
- Ciclos de emparelhamento: ≥ 750
- Temperatura de funcionamento: -10 °C a +50 °C

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	500	10.10	54.50	34.50	13.50	25,383.40
Packaging Unit Inside	50	1.01	25.00	23.00	7.00	4,025.00
Packaging Unit Single	1	0.02	2.00	7.00	12.00	168.00
Net single without Packaging	1	0.01	1.50	2.50	4.00	0.00

More images:



Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com