

# DIGITUS CAT 6A modular couplers, shielded

DN-93905  
 EAN 4016032291824



### CAT6A modular coupler, full shielded RJ45 to RJ45

Coincide com os requisitos de desempenho de canal, Classe EA ISO/IEC 11801 para até 550MHz

- 2 x RJ-45 fêmea
- Tarefa 1:1
- Versão revestida

- Material da caixa de protecção: Folha de latão - niquelado brilhante
- Material PCB: FR4, espessura 1,2mm
- Material dos contactos: Bronze fósforo
- Revestimento dos contactos: Níquel, dourado 0,6µ
- Ciclos de emparelhamento: ≥ 750
- Temperatura de funcionamento: -10 °C a +50 °C

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	500	10.10	54.50	34.50	13.50	25,383.40
Packaging Unit Inside	50	1.01	25.00	23.00	7.00	4,025.00
Packaging Unit Single	1	0.02	2.00	7.00	12.00	168.00
Net single without Packaging	1	0.01	1.50	2.50	4.00	0.00

### More images:



### Safety notes

- Protect product from moisture
- Avoid antistatic charging when installing the product
- Observe the specifications of the raw cable manufacturer during installation

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)