

# **DIGITUS Adaptador DVI**

## AK-320502-000-S EAN 4016032300496





#### DVI adapter, DVI(24+1) - DVI(24+5) M/F, DVI-D dual link, bl

This adapter is suitable to connect a DVI(24+5) cable to device or cables with DVI(24+1) connector, for example .

## Full HD, ligação dupla

• Suporta até 2560 x 1600 pixéis com 30 Hz

## Attributes

Assortment: DVI Cables Cable type: Dual-Link

- Color connector: black
- Connector 1: DVI-D, (24+1), plug

- Connector 2: DVI-J, (24+5), jack Connector surface: nickel-plated HDTV Resolution max.: 2560 x 1600 Pixel, 60Hz
- HDTV Standard: Full HD
- Hoods: molded
- Packaging: Polybag Shielding: single shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	8.20	37.00	24.00	18.00	15,984.00
Packaging Unit Inside	10	0.41	27.00	24.00	2.00	1,296.00
Packaging Unit Single	1	0.04	8.00	5.00	1.50	60.00
Net single without Packaging	1	0.04	8.00	5.00	1.50	0.00

#### More images:











#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
  operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

#### EU responsible person

 $\ensuremath{\mathsf{EU}}$  based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com