

# DIGITUS Datatransfer connection cable, D-Sub9/F - D-Sub9/F

## AK-610106-030-E EAN 4016032301141





# Datatransfer connection cable, D-Sub9 F/F, 3.0m, serial, molded, be

Datatransfer connection cable, D-Sub9,F/F, 3.0m, serial, molded, be

#### **Enables a save and stable connection**

#### **Attributes**

- Assignment: 1:1
- · Assortment: Serial Cables
- AWG: 28

- · Color cable: beige
- · Color connector: beige
- Connector 1: DSUB, 9-pin, jack
- Connector 2: DSUB, 9-pin, jack
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 3 m
- Shielding: Unshielded

| Logistics                    |                 |                |               |               |                |           |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³       |
| Packaging Unit Carton        | 50              | 9.40           | 32.00         | 29.00         | 24.00          | 22,272.00 |
| Packaging Unit Inside        | 10              | 1.88           | 36.00         | 36.00         | 8.00           | 10,368.00 |
| Packaging Unit Single        | 1               | 0.19           | 27.00         | 14.00         | 3.50           | 1,323.00  |
| Net single without Packaging | 1               | 0.17           | 17.50         | 12.00         | 3.00           | 0.00      |

#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
  operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com