



# DIGITUS Кабель-удлиннитель для передачи данных, D-Sub25/вилка - D-Sub25/розетка

AK-610201-100-E  
EAN 4016032301448



**Datatransfer extension cable, D-Sub25 M/F, 10.0m, serial/parallel, molded, be**

Datatransfer extension cable, D-Sub25,M/F, 10.0m, serial/parallel, molded, be

**Обеспечивает надежное и стабильное соединение**

**Attributes**

- Assortment: Serial and Parallel Adapters
- AWG: 26

- Color cable: beige
- Color connector: beige
- Connector 1: DSUB, 25-pin, plug
- Connector 2: DSUB, 25-pin, jack
- Connector surface: nickel-plated
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 10 m
- Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	18	14.71	45.00	32.00	25.00	36,000.00
Packaging Unit Inside	1	0.82	6.00	20.00	26.00	3,120.00
Packaging Unit Single	1	0.82	16.50	5.50	16.50	1,497.38
Net single without Packaging	1	0.68	16.50	16.50	5.00	0.00

**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)