

DIGITUS mini GBIC (SFP) Module, 1.25 Gbps, 20km

DN-81003
EAN 4016032305682



1.25 Gbps SFP Module, Singlemode, BiDi LC Simplex, Tx1310nm/Rx1550nm, up to 20km

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon, Intelinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Bidirectional WDM Module - Only one fiber is needed
- High quality and excellent reliability
- 1.25 Gbps Maximum Data Rate
- Compliant to IEEE 802.3z Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation
- MSA (Multi Source Agreement) compliant

- Hot pluggable
- Connector: 1x LC Simplex
- Wavelength: Tx 1310nm / Rx 1550nm
- Transmission Power: Minimum -5 dBm, Maximum 0 dBm
- Sensitivity receiving power: minimum -24 dBm
- For a Distance of up to 20km
- Suitable for 09/125µm Singlemode Fiber Cables
- Safe fast-locking mechanism
- 3.3V power supply
- Suitable Module for Opposite Side: DN-81004
- Operating temperature: 0 °C ~ 70 °C

Attributes

- Mode: Singlemode
- Connector: LC
- Distance (km): 20
- Wavelength: 1310/1550 nm
- DDM Support: no
- Broadcasting Mode: Biidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Gigabit


Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.02	0.00	0.00	0.00	0.00

More images:

SFP Modules						
Part Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature
250-0101	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0102	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0103	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0104	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0105	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0106	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0107	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0108	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0109	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0110	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0111	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0112	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0113	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0114	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0115	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0116	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0117	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0118	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C
250-0119	1000000000	1000000000	1000000000	LC	1310nm	0 to 70°C
250-0120	1000000000	1000000000	1000000000	LC	1550nm	0 to 70°C



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com