

DIGITUS mini GBIC (SFP) Module, 1.25 Gbps, 20km

DN-81004
EAN 4016032305729



1.25 Gbps SFP Module, Singlemode, BiDi LC Simplex, Tx1550nm/Rx1310nm, up to 20km

O módulo transceptor DIGITUS® Mini GBIC (SFP) proporciona alta qualidade e fiabilidade. Quer seja a partir de interruptor para interruptor, conversor para interruptor, conversor para conversor ou qualquer outra aplicação: a vasta gama de módulos DIGITUS® permite a utilização flexível da tecnologia de fibra ótica. A conformidade com a norma MSA (Multi Source Agreement) garante a compatibilidade com fabricantes terceiros.

A ligação de fibra ótica Plug and Play

- Módulo Mini GBIC SFP (Small Form Factor Pluggable)
- Compatível os seguintes fabricantes: Allied Telesis, Allnet, CISCO, , D-Link, Edimax, Hirschmann, Intellinet, KTI Networks, Level One, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE
- Módulo bidirecional WDM - apenas é necessária uma fibra
- Alta qualidade e excelente proteção contra falhas
- Velocidade de dados máxima de 1,25 Gbps
- Está em conformidade com a norma IEEE 802.3z Gigabit
- Produto laser de classe 1 em conformidade com a EN 60825-1
- Instalação Plug and Play simples
- Compatível com a norma MSA (Multi Source Agreement)

- Hot pluggable
- Ligação: 1x LC Simplex
- Comprimento de onda: Tx 1550 nm / Rx 1310 nm
- Potência de transmissão: Mínima -5 dBm, máxima 0 dBm
- Sensibilidade de receção: mínima -24 dBm
- Para uma distância até 20 km
- Adequado para cabo de fibra ótica 09/125 µm, modo simples
- Mecanismo de bloqueio seguro e rápido
- Fonte de alimentação 3,3 V
- Temperatura de funcionamento: 0°C-70°C

Attributes



- Mode: Singlemode
- Connector: LC
- Distance (km): 20
- Wavelength: 1550/1310 nm
- DDM Support: no
- Broadcasting Mode: Biidirectional
- Manufacturer compatibility: Universal (MSA), Cisco
- Ethernet speed: Gigabit

Package contents

- Módulo SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	9.00	11.50	3.00	310.50
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Part Number	SKU Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Model
Di-4010	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4011	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4012	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4013	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4014	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4015	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4016	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4017	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4018	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4019	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4020	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4021	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4022	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4023	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4024	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4025	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4026	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4027	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4028	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4029	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4030	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4031	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4032	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4033	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4034	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4035	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4036	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4037	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4038	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4039	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4040	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4041	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4042	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4043	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4044	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4045	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4046	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4047	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4048	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4049	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓
Di-4050	401000000000	10 Gbps	10 km	LC-Multimode Duplex	100mm	0 to 70 °C	✓

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com