

DIGITUS Adaptateur de profilé chapeau pour 1x Keystone Modul

AN-25184
EAN 4016032305859



Adaptateur de profilé chapeau pour 1x Keystone Modul

Les adaptateurs de rail DIN DIGITUS® sont destinés à recevoir les modules Keystone DIGITUS®. Ils sont disponibles en version 1 port ou 2 ports.

- Modèle de logement Keystone : sortie à 45
- domaines d'application : Coffrets de distribution électrique
- Normes en vigueur : ISO/IEC 11801 3ème édition, EN 50173-1, EIA/TIA 568-C

- Caractéristiques générales :
- Convient pour l'installation sur le rail DIN dans les boîtiers de distribution électrique
- Caractéristiques techniques :
- Matériau du boîtier vide : acier inoxydable
- Propriétés physiques :
- Température de fonctionnement : -20° C à +70 °C (ISO/IEC 11801, EN 50173-1, ANSI/TIA/EIA 568 C)

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	12.00	33.00	26.00	32.00	27,456.00
Packaging Unit Inside	20	0.48	25.00	6.00	6.00	900.00
Packaging Unit Single	1	0.02	9.00	7.00	3.00	189.00
Net single without Packaging	1	0.02	7.00	5.00	3.00	0.00

More images:



Safety notes

- Respectez les consignes du fabricant de câbles bruts lors du montage.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com