


DIGITUS Соединительный кабель HDMI High Speed с каналом Ethernet

AK-330107-100-S
EAN 4016032307051



HDMI High Speed connection cable, type A M/M, 10.0m, HDMI 1.4, gold, bl

Этот кабель поддерживает HD и 3D и используется для подключения аудио-/видеоустройств, например, проигрывателей Blu-ray, игровых приставок и т.д. к телевизору, монитору или ПК. Также подходит для использования любого приложения на базе протокола IP.

Передача аудио- и видеосигналов с качеством Full HD (1080p)


- Поддерживает 1080p при 60 Гц
- Поддержка 3D
- Поддержка технологии реверсивного звукового канала (ARC)
- Поддержка удаленного управления электронными устройствами (CEC)
- Поддержка Lip-Sync (синхронизация звука и изображения)
- Поддержка Dolby TrueHD
- С каналом Ethernet (HEC)

Attributes

- Assortment: HDMI Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- HDMI Standard: High Speed HDMI with Ethernet
- HDTV Resolution max.: 1920 x 1200 Pixel, 60Hz
- HDTV Standard: Full HD
- Hoods: molded
- Packaging: Polybag
- Wire material: CU
- Length: 10 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	22	14.26	45.00	32.00	25.00	36,000.00
Packaging Unit Inside	1	0.65	5.00	23.00	27.00	3,105.00
Packaging Unit Single	1	0.65	32.00	23.00	2.00	1,472.00
Net single without Packaging	1	0.64	28.00	20.00	5.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com