

DIGITUS DIGITUS цветные монтажные шнуры, SC OM2 50/125 μ, Simplex

DK-25221-02-4
EAN 4016032308782



FO pigtail set, 12 pcs., SC, MM OM4 50/125 μ loose buffer, color code DIN IEC 304, 2 m

The DIGITUS® Fiber Optic Colored Pigtails are available as LC Simplex, SC Simplex and ST Simplex version and offer with the classes OS2, OM2, OM3 and OM4 best performance and link quality for your network. The connector conforms acc. IEC 61754-4 2002 and is equipped with a Zirconia ceramic ferrule. The colored buffers are color coded according to IEC 304 (white, violet, turquoise, black, red, pink, orange, gray, green, yellow, brown, blue).

Отличная производительность и качество связи для Вашей сети.

- Стандартный разъем согл. IEC 61754-4 2002
- Окрашенный буфер, согласно IEC 304, цвета - белый, фиолетовый, бирюзовый, чёрный, красный, розовый, жёлтый, коричневый, синий
- 12 шт. в упаковке
- свободный буфер
- Обратное затухание MM ПК: > 25 дБ

- Втулка из циркониевой керамики
- Simplex OM 2 50/125μ 2 м
- Диаметр сердцевины: Ш 0,9 ± 0,1 мм
- Основная оболочка: акрил; Ш 250± 15μм
- Окрашенный буфер, согласно IEC 304, цвета - белый, фиолетовый, бирюзовый, чёрный, красный, розовый, жёлтый, коричневый, синий
- 12 шт. в упаковке
- свободный буфер

Attributes

- Boot: single-color
- Cable jacket: LSOH
- Connector 1: SC
- Fiber class: OM4
- Fiber diameter: 50/125μ
- Mode: Multimode
- Length: 2 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	160	16.00	41.00	41.00	28.00	47,068.00
Packaging Unit Inside	20	2.00	19.00	19.00	12.00	4,332.00
Packaging Unit Single	1	0.10	17.00	17.00	1.00	289.00
Net single without Packaging	1	0.05	15.00	15.00	1.00	0.00

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com