

# DIGITUS Gigabit Ethernet PCI Network Card

**DN-10110**  
**EAN 4016032310778**



**Gigabit Ethernet PCI Card 32-bit, low profile bracket, RTL8169SC chipset**

Gigabit Ethernet PCI Card, 32-bit, low profile bracket, RTL8169SC chipset

**Unprecedented speed is now available over your existing network cabling - Built to run the fastest network applications**

- Supports 10/100/1.000 Mbps auto negotiation
- IEEE 802.3, IEEE 802.3u, IEEE 802.3ab compatible
- IEEE 802.3x full-duplex and flow control
- Supports Autonegotiation and Crossover detection
- Realtek Chipset
- PCI Local Bus Master Rev.2.1 and 2.2 compatible
- Suitable for all common network environments
- Additional Low Profile Bracket to use the Card also in Thin Computers
- Operating temperature: 0 °C - 70 °C
- Operating humidity: 25% - 65% RH (non-condensing)
- Supports Windows 10, 8.1, 8, 7, Vista, XP, Mac OS X and Linux

- Chipset: Realtek RTL8169SC Gigabit Ethernet Controller
- Bus: PCI V2.2, 32/64-bit, 33/66MHz
- IEEE802.3, IEEE802.3u, and IEEE802.3ab compliant.
- Support for IEEE802.3x Full-Duplex flow control
- Support IEEE802.1Q Virtual LAN (VLAN) Tag
- Complaint to PC97, PC98, PC99 and PC2001 standards
- Auto-Negotiation support for Auto-Detect 10/100/1000Mbps data rate and Full/Half-Duplex operation mode
- Support ACPI and PCI power management
- Automatic crossover support for crossover or regular cable
- Support Boot ROM function (optional)
- Support Wake on LAN function
- One RJ-45 Port

**Package contents**

- Gigabit Ethernet PCI network card
- Low profile bracket
- Quick installation guide
- Product support CD-ROM

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 40           | 6.30        | 38.00      | 41.00      | 41.00       | 63,878.00       |
| Packaging Unit Inside        | 1            | 0.16        | 5.50       | 18.00      | 18.60       | 1,841.40        |
| Packaging Unit Single        | 1            | 0.16        | 5.50       | 18.00      | 18.60       | 1,841.40        |
| Net single without Packaging | 1            | 0.05        | 12.10      | 11.50      | 1.90        | 0.00            |

**Safety notes**

- Switch off the computer completely and disconnect it from the power supply before installing or removing the network card.
- Static discharge can damage the product or the PC. Take measures against static discharge (ESD) when installing the product, e.g. wear an antistatic wrist strap.
- Before installation, touch the metal surface of the PC housing or another grounded object to ground any ESD charge via the housing.
- Avoid using too much force when connecting the product to the PC.
- Please ensure that any cables are connected correctly without overstretching or damaging them.
- Avoid touching the contacts of the product with your fingers to prevent corrosion or static charge.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)