

# **DIGITUS Italian power cord connection cable**

## AK-440113-018-S EAN 4016032312086





#### Power Cord, Italy plug - C13 M/F, 1.8m, H05VV-F3G 0.75qmm, bl

This power cord used for the connection of a PC or monitor to the Italian indoor power supply system (outlet).

#### Corresponds to the Italian guidelines

- Assortment: Device Connection Cables
- Cable standard: H05 VV F3G
- Color cable: black
- Color connector: black
- · Connector 1: CEI 23-50, plug

- Connector 2: IEC C13, jack
- · Connector surface: nickel-plated
- Current load capacity: 250V/10A
- Hoods: molded
- Lead cross-section: 0.75qmm
- Packaging: Polybag
- Wire material: CU
- Length: 1.8 m
- · Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	80	15.20	50.00	32.50	23.00	37,375.00
Packaging Unit Inside	10	1.90	8.00	23.00	30.00	5,520.00
Packaging Unit Single	1	0.19	2.00	18.00	20.00	720.00
Net single without Packaging	1	0.19	2.00	18.00	20.00	0.00

#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
  operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com