

DIGITUS Соединительный кабель HDMI High Speed с каналом Ethernet

AK-330114-020-S
EAN 4016032322979



HDMI Standard connection cable, type A M/M, 2.0m, w/Ethernet, Full HD, gold, bl

Этот кабель поддерживает HD и 3D и используется для подключения аудио-/видеоустройств, например, проигрывателя Blu-ray, игровых приставок и т.д. к телевизору, монитору или ПК.

Поддерживает Ultra HD 4K и 3D и предлагает возможность связи с сетью Ethernet.

- Поддерживает 4K 30 Гц
- Поддерживает Ultra HD 4K
- HDMI 1.4
- 8.16 Gbps
- Поддержка 3D
- Поддержка технологии реверсивного звукового канала (ARC)
- Поддержка удаленного управления электронными устройствами (CEC)
- Поддержка Lip-Sync (синхронизация звука и изображения)



- Поддержка Dolby TrueHD
- С каналом Ethernet (HEC)

Attributes

- Assortment: HDMI Cables
- Color cable: black
- Color connector: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold flash
- HDMI Standard: High Speed HDMI with Ethernet
- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Length: 2 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	11.50	25.00	32.00	45.00	36,000.00
Packaging Unit Inside	1	0.10	23.00	20.00	1.00	460.00
Packaging Unit Single	1	0.10	2.00	14.00	25.00	700.00
Net single without Packaging	1	0.00	1.50	10.00	13.00	0.00

More images:



Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com