

DIGITUS Comutador VGA DIGITUS 2 PCs, 1 Monitor

DS-44100-1
EAN 4016032323532



VGA Switch, 2 inputs, 1 output 250MHz, incl. power supply, DC9V, 300mA, 1080p

O comutador de vídeo VGA é a solução ideal para a ligação e a comutação de vários PCs num monitor. A mudança de ligações dos cabos deixa de ser necessária, pois o comutador de vídeo VGA permite a seleção simples da fonte de vídeo a ser mostrada, bastando para isso premir o botão. Adicionalmente, o comutador dispõe de uma função de áudio através da qual os sinais de vídeo e de áudio podem ser simultaneamente transmitidos.

Fácil e prática selecção de fonte de vídeo através de botão de pressão

- Ideal para salas de aula, ações de formação, salas de formação, etc.
- 2 entradas (PC), 1 saída (monitor, projector, etc.)
- Resolução máx.: 1920x1080p @60Hz
- Banda larga de vídeo 250MHz

- Suporta DDC, DDC2, DDC2B
- Ligações de entrada de vídeo: HDSUB15/Fêmea
- Ligações de saída de vídeo: HDSUB15/Fêmea
- Entrada de áudio: 1 x conector fêmea de 3,5 mm
- Saída áudio: 2 x conector fêmea de 3,5 mm
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Number of ports: 2
- Signal input: VGA
- Signal output: VGA

Package contents

- Comutador VGA 250MHz, 2 entradas, 1 saída
- Adaptador de corrente
- Manual de instruções

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	10	8.30	32.00	28.00	33.00	29,568.00
Packaging Unit Inside	1	0.83	6.00	25.50	15.00	2,295.00
Packaging Unit Single	1	0.83	6.00	25.50	15.00	2,295.00
Net single without Packaging	1	0.57	9.00	13.80	4.00	0.00

More images:



Safety notes

- If the device is powered by a plug-in power supply, ensure that the power adapter is connected correctly and meets the specified requirements (e.g. voltage and current).
- Only use certified CAT5e or CAT6 cables to ensure stable signal transmission.
- For particularly long cable runs or in environments prone to interference, it is recommended to use shielded network cables.
- Make sure that all connections are tight and secure to avoid loose contacts that could affect the signal quality. Make sure that the HDMI and Ethernet connections are connected correctly.
- Make sure that the CAT cable is not laid near high-voltage power lines or other strong sources of electromagnetic interference to avoid signal interference.
- Only operate the device within the specified temperature range.
- Do not use the device outdoors or in damp or wet environments
- Check all connections and cables regularly for wear or damage. Cables and connections can wear out, especially with frequent use or long installations, which can lead to poor signal quality or system failure.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com