

DIGITUS Repartidor VGA 350MHz, 2 portas

DS-41120-1
EAN 4016032323839



DIGITUS VGA Splitter, 2port, plastic housing 350 MHz, HDSUB 15/M -> 2x HDSUB 15/F, 1080p

Com um repartidor de vídeo pode usar uma fonte de vídeo para exibir imagens semelhantes em 2, 4, 8 ou 16 monitores - ou ainda em mais ecrãs por meio de menu em cascata. Portanto, pode ser usado um repartidor de vídeo em vários campos de aplicação, por ex. instalações de bancadas de ensaio, centros de dados, suporte técnico, transmissão de vídeo, apresentações e instalações educativas.

Permite a exibição em simultâneo de dois monitores diferentes - ideal para salas de aula, feiras ou demonstrações em estabelecimentos comerciais

- Caixa de plástico
- Largura de banda de vídeo: 350MHz

- Suporta DDC, DDC2, DDC2B
- Autônomo (máx. 64)
- Distância transmissão máx.: 75m
- Vídeo IN/OUT: HD DSUB, 15-pinos, tomada
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Number of ports: 2
- Signal input: VGA
- Signal output: VGA

Package contents

- Repartidor VGA 350MHz, 2 portas
- Manual de instruções

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	8.40	28.50	33.00	32.00	30,096.00
Packaging Unit Inside	1	0.14	3.20	13.50	10.50	453.60
Packaging Unit Single	1	0.14	3.20	13.50	10.50	453.60
Net single without Packaging	1	0.09	6.50	6.50	2.00	0.00

More images:



