

# DIGITUS VGA Splitter 350MHz, 2-Port

DS-41120-1  
EAN 4016032323839



**VGA Splitter, 2port, plastic housing 350 MHz, HDSUB 15/M -> 2x HDSUB 15/F, 1080p**

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

**Provides simultaneous display on two different monitors - Perfect for classrooms, tradeshows, or in-store displays**

- Plastic housing
- Video bandwidth: 350MHz
- Max. resolution: 1920x1080p

- DDC, DDC2, DDC2B support
- Cascadable (max. 64)
- Max. transmission distance: 75m
- Video IN/OUT: HD DSUB, 15-pin, jacks
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Number of ports: 2
- Signal input: VGA
- Signal output: VGA

**Package contents**

- VGA Splitter 350 MHz, 2-Port
- Manual

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 60           | 8.40        | 28.50      | 33.00      | 32.00       | 30,096.00       |
| Packaging Unit Inside        | 1            | 0.14        | 3.20       | 13.50      | 10.50       | 453.60          |
| Packaging Unit Single        | 1            | 0.14        | 3.20       | 13.50      | 10.50       | 453.60          |
| Net single without Packaging | 1            | 0.09        | 6.50       | 6.50       | 2.00        | 0.00            |

**More images:**



