

DIGITUS VGA Splitter 350MHz, 2-Port

DS-41120-1
EAN 4016032323839



VGA Splitter, 2port, plastic housing 350 MHz, HDSUB 15/M -> 2x HDSUB 15/F, 1080p

With a video splitter you can use one video source to display identical images on 2, 4, 8, or 16 monitors - or on even more screens by means of cascading. Thus, a video splitter can be used in various application fields, e.g. test bench facilities, data centers, help desks, video broadcasting, presentations and educational facilities.

Provides simultaneous display on two different monitors - Perfect for classrooms, tradeshows, or in-store displays

- Plastic housing
- Video bandwidth: 350MHz
- Max. resolution: 1920x1080p

- DDC, DDC2, DDC2B support
- Cascadable (max. 64)
- Max. transmission distance: 75m
- Video IN/OUT: HD DSUB, 15-pin, jacks
- HDTV Resolution max.: 1920 x 1080 Pixel, 60Hz
- HDTV Standard: Full HD
- Number of ports: 2
- Signal input: VGA
- Signal output: VGA

Package contents

- VGA Splitter 350 MHz, 2-Port
- Manual

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	60	8.40	28.50	33.00	32.00	30,096.00
Packaging Unit Inside	1	0.14	3.20	13.50	10.50	453.60
Packaging Unit Single	1	0.14	3.20	13.50	10.50	453.60
Net single without Packaging	1	0.09	6.50	6.50	2.00	0.00

More images:



