

DIGITUS DIGITUS mini GBIC (SFP) модуль, 10 Гбитс, 10.0 км

DN-81201
EAN 4016032324140



10G SFP+ Module, Singlemode, DDM LC Duplex Connector, 1310nm, up to 10km

Модули трансиверов DIGITUS® Mini GBIC (SFP) обеспечивают наивысшее качество и надежность. Будь то соединение между коммутаторами, между конвертером и коммутатором, между конвертерами или другие, обширные возможности применения: Большое разнообразие модулей DIGITUS® позволяет гибко использовать технологию стекловолокна. Благодаря соответствию стандарту MSA (Multi Source Agreement) обеспечивается совместимость с о сторонними производителями.

Стекловолоконное соединение Plug and Play

- Модуль Mini GBIC SFP (компактный приёмопередатчик)
- Совместим с устройствами следующих производителей: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Поддерживает DDM (Digital Diagnostic Monitoring)
- Высокое качество и максимальная отказоустойчивость
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Класс 1 лазерный продукт по EN 60825-1

- Простая установка Plug and Play
- Совместим со стандартом MSA (сетевое соглашение)
- С возможностью оперативной замены
- Тип подключения: 1 дуплекс LC
- Длина волны: 1310 нм
- Мощность передатчика: не менее -8 дБм, макс. -0,5 дБм
- Чувствительность приемника, не менее -12.5 дБм
- Для расстояния до 10 км
- Надежный быстродействующий механизм
- Рабочая температура: 0-70 °C

Attributes

- Mode: Singlemode
- Connector: LC
- Distance (km): 10
- Wavelength: 1310 nm
- DDM Support: yes
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: 10 Gigabit

Package contents

- Модуль SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	20	2.00	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.10	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.10	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:



SFP Modules						
Part Number	SKU Code	Speed	Distance	Connector	Mounting	Operating Temperature
2849480	401000000001	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000002	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000003	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000004	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000005	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000006	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000007	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000008	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000009	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000010	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000011	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000012	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000013	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000014	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000015	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000016	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000017	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000018	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000019	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000020	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000021	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000022	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000023	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000024	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000025	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000026	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000027	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000028	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000029	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000030	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000031	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000032	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000033	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000034	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000035	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000036	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000037	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000038	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000039	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000040	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000041	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000042	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000043	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000044	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000045	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000046	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000047	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000048	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000049	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C
2849480	401000000050	10 Gbps	10 km	LC Duplex Small Form-factor Pluggable	100mm	-40 to 75 °C



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage
- eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com