


DIGITUS Cabo de alimentação Y interno

AK-430400-002-M EAN 4016032325123





Internal Y-power supply cable 0.20m, IDE - 2x IDE connector

You can never have enough power connections. Whether disk drives, fans, lighting or other consumers, these adaptors doubles the connection at power supply unit for two 13.3 cm (5.25) disk drives.

Ligação e alimentação seguras

• IDE plug (13,4cm/5.25") <=> 2x IDE jack (13,4cm/5.25")

Attributes

• Assortment: Internal Power Supply Cables

- AWG: 18
- · Color cable: various
- Color connector: transparent
- Connector 1: IDE (5,25") power plug
- Connector 2: 2x IDE (5,25") power jack
- · Hoods: plastic
- Wire material: CU
- Length: 0.2 m
- · Shielding: Unshielded

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	500	13.87	38.00	30.50	32.00	37,088.00
Packaging Unit Inside	10	0.28	5.00	14.00	16.00	1,120.00
Packaging Unit Single	1	0.03	10.50	9.50	2.00	199.50
Net single without Packaging	1	0.02	10.00	9.00	1.50	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- · Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- · Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum
 operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com