

1

# DIGITUS Cabo de ligação USB 3.0

AK-300117-003-S EAN 4016032325574





### USB 3.0 connection cable, USB A - Micro USB B M/M, 0.25m, USB 3.0 conform, bl

Cabo ligação USB3.0 para ligação dum controlador USB ou dispositivo USB (com Micro B fêmea) para porta USB PC, transferência de dados até 5000 Mbps (Super-Velocidade).

## Attributes

- Assortment: USB Cables
- AWG: 28
- . Color cable: black
- Color connector: black •

- Connector 1: USB A, plug
- Connector 2: Micro USB B, plug • •
- Connector surface: nickel-plated Ferrite filter: none •
- •
- Hoods: molded . Packaging: Polybag
- USB compliance: USB 3.0 / 3.1 •
- Wire material: CU •
- . Length: 0.25 m
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	200	7.50	38.00	33.00	24.00	30,096.00
Packaging Unit Inside	10	0.38	3.00	34.00	38.00	3,876.00
Packaging Unit Single	1	0.04	1.00	10.00	20.00	200.00
Net single without Packaging	1	0.04	1.00	10.00	20.00	0.00

## More images:







### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

# EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com