

DIGITUS DisplayPort Connection Cable

AK-340100-100-S
EAN 4016032329978



DisplayPort Connection Cable, Type DP M/M, 10.0m, w/interlock, UHD 4K, DP 1.2, bi

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Support 1080p with 30Hz
- Max. supported Video Resolution: 1920 x 1080 p with 60 Hz
- Supported transmission modes: RBR, HBR, HBR2
- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 10 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	16	9.90	50.00	35.00	35.00	61,250.00
Packaging Unit Inside	1	0.62	5.50	18.00	29.00	2,871.00
Packaging Unit Single	1	0.62	5.50	18.00	29.00	2,871.00
Net single without Packaging	1	0.62	5.50	18.00	29.00	0.00

More images:

