

# DIGITUS Модульный соединительный спиральный кабель UAE

AK-460101-020-S  
EAN 4016032330110



**UAE connection cable, RJ10 M/M, 2.0m, CU, 4x7x0,12mm, flat, helic, bl**

Этот модульный спиральный кабель может использоваться для соединения телефонной трубки с телефоном и служит идеальным заменителем для слишком коротких / длинных или неисправных кабелей телефонной трубки.

**Высокоэластичный и гибкий**

- Модульный штекер RJ10, 4P4C <=> Модульный штекер RJ10, 4P4C
- Пластиковый штекер, прозрачный
- Разводка 1:1
- Спиральный 4-ех жилый кабель
- Цвет: черный

#### Attributes

- Assortment: Telecommunication Cables
- Length: 2 m

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	400	13.33	44.50	40.00	26.00	46,280.00
Packaging Unit Inside	10	0.33	19.50	13.50	6.00	1,579.50
Packaging Unit Single	1	0.03	1.50	14.00	20.00	420.00
Net single without Packaging	1	0.03	38.00	5.00	1.10	0.00

#### More images:



#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product specifications for the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)