

# DIGITUS DisplayPort Connection Cable

**AK-340100-150-S**  
**EAN 4016032330776**



**DisplayPort Connection Cable, Type DP M/M, 15.0m, w/interlock, UHD 4K, DP 1.2, bl**

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

**Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.**

- Support 1080p with 30Hz
- Max. supported Video Resolution: 1920 x 1080 p with 60 Hz
- Supported transmission modes: RBR, HBR, HBR2
- HDCP-Version: HDCP 1.3
- Assortment: DisplayPort Cables
- AWG: 28
- Color cable: black

- Color connector: black
- Connector 1: DP, plug
- Connector 2: DP, plug
- Connector surface: nickel-plated
- DisplayPort standard: DisplayPort 1.1a
- Ferrite filter: none
- HDTV Standard: Full HD
- Hoods: molded
- Interlock: Snap fastener
- Packaging: Polybag
- Wire material: CU
- Length: 15 m
- AOC - Active Optical Cable: no
- Shielding: triple shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	10	9.20	36.50	33.00	20.00	24,090.00
Packaging Unit Inside	1	0.92	7.00	22.00	28.50	4,389.00
Packaging Unit Single	1	0.92	19.00	19.00	5.00	1,805.00
Net single without Packaging	1	0.92	7.00	22.00	28.50	0.00

**More images:**

