

DIGITUS HDMI High Speed connection cable with Ethernet and signal amplifier

AK-330118-100-S
EAN 4016032336617



HDMI High Speed Connection Cable, Type A, w/amp. M/M, 10.0m, Ultra HD, 4K@30Hz, gold, bl

This active HDMI cable is ideal for transmitting high-bandwidth video and audio data over long distances. With the integrated signal amplifier it guarantees loss-free transmission over the entire cable length with UHD resolutions of up to 4K/30Hz. The ideal application for home, meeting or conference rooms as well as inside buildings are only some of the fields of application. The user-friendly installation is simply plug and play, plug in and enjoy the highest image quality immediately. Numerous standards are supported, e.g. HEC, CEC as well as Full HD 3D HFR, Deep Color and Multistream support. In the audio area, ARC, DTS-HD Master Audio or Dolby TrueHD are supported, among others, as well as many other features.

UHD-compatible HDMI cable with signal amplifier and Ethernet support (HEC)

- Supports HDMI 1.4 features
- Supports up to 4K / 30 Hz (3840 x 2160p)
- Supported Audio format: DVD-Audio, SACD, Dolby Digital Plus, TrueHD and dts-HD
- Support of 3D with 1080p resolution
- With Ethernet Channel (HEC)
- Supports 1080p 3D HFR
- Supports Deep Color 30bit

- Supports Audio Return Channel (ARC)
- Supports Consumer Electronic Control (CEC)
- Supports Lip-Sync (Audio/Video Synchronisation)
- Supports Multi Stream Audio/Video
- Supports 32-Kanal Audio
- Supports Blu-Ray und HD-DVD Audio/Video
- Supports EDID 2.0 (Device detection)
- Supports DVI Version 1.0
- Operating temperature: -10 ~ 50°C
- Operating humidity: 10 - 80% RH
- Assortment: HDMI Cables
- AWG: 28
- Color cable: black
- Color connector: black
- Connector 1: HDMI type A, plug
- Connector 2: HDMI type A, plug
- Connector surface: gold-plated
- HDMI Standard: High Speed HDMI with Ethernet
- HDTV Resolution max.: 3840 x 2160 Pixel, 30Hz
- HDTV Standard: Ultra HD 4K
- Hoods: molded
- Wire material: CU
- Length: 10 m
- AOC - Active Optical Cable: no
- Shielding: Double shielding

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	15	10.30	51.00	34.00	21.00	36,414.00
Packaging Unit Inside	1	0.69	6.00	14.00	14.00	1,176.00
Packaging Unit Single	1	0.69	6.00	14.00	14.00	1,176.00
Net single without Packaging	1	0.00	6.00	14.00	14.00	0.00

More images:

