

# DIGITUS Network Rack Unique Series - 600x600 mm (WxD)

DN-19 26U-6/6-B-1  
EAN 4016032343592



**26U network rack, Unique 1342x600x600 mm, color black (RAL 9005)**

The network cabinets from the Unique series were developed for especially convenient and flexible network cabling. Inlets in the roof and floor equipped with brushes (starting with 26 rack units and a cabinet width of 800 mm), a sliding inlet in the floor structure with foam rubber seal and brush management panels on the back above and below the rear door (starting with 26 rack units) enable versatile use in a wide range of application scenarios. Vertical cable channels with brackets installed next to the profile rails (starting with a cabinet width of 800 mm) round off the design. An offset, removable cover with ventilation slits ensures enhanced air circulation. This features a special design for easy mounting of a fan module. Two pairs of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth is adjustable and they are connected to additional depth bars in the cabinet. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Side walls and doors that can be locked or removed in a modular design improve accessibility. The door hinges can be switched. Furthermore, the cabinets can be completely dismantled if necessary due to their collapsible design.

**The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany**

- Safety class rating IP20
- Lateral metal struts front door with safety glass
- Lock system with pivot lever on front door (ready for profile half cylinder; adapter included)
- 120° door opening angle on front- and rear doors
- Single wing opening rear door
- 1-point-locking-mechanism on all doors

- Side panels are lockable and removable
- incl. 4 pieces of leveling feet already pre-configured under the rack
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Built-in depth support bars for more stability
- Sliding cable entry with rubber sealing on the base
- Cable entry with brush strip at the top and bottom of the cabinet rear side
- Special roof construction for fan unit with added lid which can be unmounted
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Equipment mounting depth min.-max.: 363-543 mm
- Rack is completely mounted
- Cabinet type: Network cabinet
- Color: black, RAL 9005
- Depth: 600 mm
- Front door: Glass door, single opening
- Load capacity: 800 kg
- Rear door: Steel door and cable entry, single opening
- Side panels: Both sides
- Units: 26
- Width: 600 mm
- IP protection class: IP20
- Mounted: yes

**Package contents**

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- Installation Kit for Profile Half Cylinder
- 2 x keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	61.00	68.00	68.00	148.00	684,352.00
Packaging Unit Inside	1	61.00	68.00	68.00	148.00	684,352.00
Packaging Unit Single	1	61.00	68.00	68.00	148.00	684,352.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:

**DW-19 26U-6/6-B-1** // Network Cabinet Unique Series, 26U, 600x600mm (WxD)

**Hauptmerkmale**  
Key Features

- Steel
  - Special construction for fan-unit assembly
  - Top cover with drainage screen for protection on fire
- Vertical cable management ducts
  - with shutters
  - on cabinet front bottom width
- Side panels
  - lockable and detachable
- Cable entries
  - lockable left and right (top and base)
  - includes front 80mm width
  - locking entry with foam cover on the base
  - lockable on top and base part of rear door
  - (shown 26U)

482.6 mm (19") profile rails  
800kg load capacity

Steel front door with safety glass  
120° clear opening angle  
swinghandle ready for profile lock cylinder

