

DIGITUS Cat.6A U/FTP installation cable, 500 m, simplex, Eca

DK-1623-A-VH-5
EAN 4016032344216



CAT 6A U-FTP installation cable, 500 MHz Eca (EN 50575), AWG 23/1, 500 m drum, sx, blue

The Digitus® Cat.6A U/FTP installation cable is characterized by the following cable construction 4x2x AWG23/1 and reaches a transmission frequency up to 500 MHz. The halogen free cable jacket is conform to the standard IEC 60332-1, FRNC-B, LSZH-1 and CPR Euro class Eca. The cable is suitable for building structured cabling in the secondary and tertiary area. Compliant with the following standards ISO/IEC 11801, DIN EN 50173, DIN EN 50288-10-1.


Future-oriented standards and high-end quality for your network.

- Physical properties:
- Conductor: Bare annealed copper, solid AWG 23/1
- System/s of AVCP: AVCP 3
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Individual pair shielding: Aluminum foil, providing 100 % coverage
- Overall shielding: None, with drain wire
- Outer sheath: Eca to B2ca acc. to EN 50575; LSZH
- Outer sheath color: Light blue (RAL 5012)
- Mechanical properties:
- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +60 °C
- Operating temperature range: -20 °C up to +75 °C

- Installation temperature range: 0 °C up to +50 °C
- Overall diameter Simplex (nominal): 7.0 (Eca); 7,2 mm (Dca); 7,6 mm (Cca); 7,6 mm (B2ca)
- Weight (kg/km): 56 kg (Eca); 57 kg (Dca); 58 kg (Cca); 58 kg (B2ca)
- Electrical properties:
- Impedance: 100±15 Ohm @ 4 - 100MHz; 100±25 Ohm @100-500 MHz
- Capacitance: 45 pF/m nominal @ 1 KHz
- Capacitance unbalance (pair-ground): 1.6 pF/m max. @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC loop resistance: 190 Ohm/km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: CA-Type 2
- Signal propagation delay: 450 nS/100 m max.
- Propagation delay: 15 nS/100 m max.
- Separating class: "c" acc. to EN 50174-2
- NVP: 70%
- Assortment: Twisted Pair Installation Cables
- Category: CAT 6A
- Shielding: U-FTP, pairs in metal foil
- CPR: Eca
- Length: 500 m
- Color: light-blue
- Jacket: LSOH
- Structure: 4 x 2 AWG 23/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	28.00	40.00	30.00	30.00	36,000.00
Packaging Unit Inside	1	28.00	40.00	30.00	30.00	36,000.00
Packaging Unit Single	1	28.00	40.00	30.00	30.00	36,000.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



DIGITUS

AWG 23/1 | 500 MHz | 10 Gbit Ethernet | CAT 6a | Eca | LSZH | CPRI class

CAT 6a U/FTP Installation Cable, 500m, Simplex, Eca

DIGITUS

DK-1623-A-VH-S // CAT 6, U/FTP Installation Cable, 500m, Simplex, Eca

Anwendungsbeispiel
Example of use

DIGITUS

DK-1623-A-VH-S // CAT 6, U/FTP Installation Cable, 500m, Simplex, Eca

Kabelquerschnitt
Cable cross section

DIGITUS

Produktinformationen / Product Information	Physikalische Spezifikationen / Physical Properties
Herstellername / Manufacturer: DIGITUS Professional	Typ / Type: CAT 6a U/FTP Installation Cable
Produktcode / Product Code: DK-1623-A-VH-S	Material / Material: Polyethylene (PE) jacket, PVC insulation
Produktbeschreibung / Product Description: CAT 6a U/FTP Installation Cable, 500m, Simplex, Eca	Leistungsfähigkeit / Performance: 10 Gbit Ethernet, 500 MHz, AWG 23/1
Technische Eigenschaften / Technical Properties: LSZH, CPRI class	Mechanische Eigenschaften / Mechanical Properties: Bending radius, tensile strength, etc.

DIGITUS

Leistungseigenschaften / Performance Properties

Parameter	Value
Attenuation (dB/100m)	1.5
Return Loss (dB)	15
Shielding Effectiveness (dB)	100
Temperature Range (°C)	-20 to 70

Intertek

ETL Verified Certificate of Compliance Number: 1942299RST-011

Approved for use in the United States of America for the following applications:

- Category 6 U/FTP Ethernet Network Cables
- Category 6a U/FTP Ethernet Network Cables

GHMT

Certificate No. 19884-21

Zertifikat No. 19884-21

Category 6a

Kategorie 6a

GHMT Type Approval

DIGITUS

DIGITUS

Performance comparison table:

Category	Shielding	Performance
B2ca	None	1+
Cca	None	2
Dca	None	3
Eca	None	3

