

# DIGITUS DIGITUS® Network Cabinet Unique Series - 800x800 mm (WxD)

DN-19 22U-8/8-B-1  
EAN 4016032344322



### 22U network rack, Unique 1164x800x800 mm, color black (RAL 9005)

The network cabinets from the Unique series were developed for especially convenient and flexible network cabling. Inlets in the roof and floor equipped with brushes (starting with 26 rack units and a cabinet width of 800 mm), a sliding inlet in the floor structure with foam rubber seal and brush management panels on the back above and below the rear door (starting with 26 rack units) enable versatile use in a wide range of application scenarios. Vertical cable channels with brackets installed next to the profile rails (starting with a cabinet width of 800 mm) round off the design. An offset, removable cover with ventilation slits ensures enhanced air circulation. This features a special design for easy mounting of a fan module. Two pairs of galvanized 483 mm (19") profile rails labeled with rack units readable in both directions are installed on the inside. Their depth is adjustable and they are connected to additional depth bars in the cabinet. Each cabinet is made of up to 1.5 mm thick sheet steel. Coloring is done with electrostatic powder coating in the standard colors gray (RAL 7035) or jet black (RAL 9005). Side walls and doors that can be locked or removed in a modular design improve accessibility. The door hinges can be switched. Furthermore, the cabinets can be completely dismantled if necessary due to their collapsible design.

### The DIGITUS® Unique Series is made for high demand IT-Infrastructure Solutions - designed and developed on highest standard in Germany

- Safety class rating IP20
- Complete metal frame front door with safety glass
- Lock system with pivot lever on front door (ready for profile half cylinder; adapter included)
- 120° door opening angle on front- and rear doors
- Double wing opening rear door
- 1-point-locking-mechanism on all doors


- Side panels are lockable and removable
- incl. 4 pieces of leveling feet already pre-configured under the rack
- 483 mm (19") profile rails mounted on the front- and rear side inside of the rack, galvanized
- 483 mm (19") profile rails are adjustable in depth and with height unit marking
- Sliding cable entry with rubber sealing on the base
- Top and base with brushed cable entries left and right
- Special roof construction for fan unit with added lid which can be unmounted
- Several earthing points for rack components
- Incl. installation set (screws, cage nuts, washers)
- Equipment mounting depth min.-max.: 563-743 mm
- Rack is completely mounted
- With vertical cable management ducts in the front
- Cabinet type: Network cabinet
- Color: black, RAL 9005
- Depth: 800 mm
- Front door: Glass door, single opening
- Load capacity: 800 kg
- Rear door: Steel door, closed, double opening
- Side panels: Both sides
- Units: 22
- Width: 800 mm
- IP protection class: IP20
- Mounted: yes

### Package contents

- Earthing wire set
- Installation set (screws, cage nuts, washers)
- Installation Kit for Profile Half Cylinder
- 2 x keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	69.00	85.00	85.00	121.40	877,115.00
Packaging Unit Inside	1	69.00	85.00	85.00	121.40	877,115.00
Packaging Unit Single	1	69.00	85.00	85.00	121.40	877,115.00
Net single without Packaging	1	68.00	80.00	80.00	116.40	0.00

More images:



**DN 19 22U-8/BB-1 // Network Cabinet Unique Series, 22 U, 800x800mm (WxD)**

**Hauptmerkmale**  
Key Features

- Vertical cable management ducts**
  - with shutter
  - in cabinet from 400mm width
- Steel front door with safety glass**
  - 130° door opening angle
  - emergency ready for profile lock cylinder
- Side panels**
  - includes and detachable

- Roof**
  - special construction for fan unit assembly
  - has cover with distance screen for addressed air flow
- 682,6 mm (19") profile rails**
  - 800kg load capacity
- Cable entries**
  - includes left and right stop and bend on cabinet
  - from 400mm depth
  - locking only with force cover on the base
  - position on top and base part of rear door