

# **DIGITUS VGA Monitor Connection Cable**

AK-310103-030-S EAN 4016032344889





## VGA Monitor connection cable, HD15 M/M, 3.0m, 3Coax/7C, 2xferrite, bl

For connection of a PC, for example, with a monitor or beamer /projector.

Offers high-quality protection against external interferences and prevents ghost images and other image faults.

- Support 1280 x 1024 pixel with 60Hz
- 3 x Coax for RGB and 7 x AWG28 signal wires
- 2 x ferrite filters

#### Attributes

- Assortment: VGA Cables
- AWG: 28

- Cable type: 3Coax + 7-wire
- Color cable: black
- Color connector: black
- Connector 1: HD DSUB, 15-pin, plug
- Connector 2: HD DSUB, 15-pin, plug
- Connector surface: nickel-plated
- Display Data Channel: DDC2Ferrite filter: 2 x ferrite beads
- Ferrite filter: 2 x ferrite beads
   Hoods: molded
- Hoods: molded
- Packaging: PolybagWire material: CU
- Wre materia
  Length: 3 m
- Shielding: Double shielding

| Logistics                    |                 |                |               |               |                |           |
|------------------------------|-----------------|----------------|---------------|---------------|----------------|-----------|
|                              | Number<br>(pcs) | Weight<br>(kg) | Depth<br>(cm) | Width<br>(cm) | Height<br>(cm) | cm³       |
| Packaging Unit Carton        | 30              | 10.50          | 39.00         | 31.00         | 24.00          | 29,016.00 |
| Packaging Unit Inside        | 10              | 3.50           | 15.00         | 31.00         | 31.00          | 14,415.00 |
| Packaging Unit Single        | 1               | 0.35           | 5.00          | 14.00         | 22.00          | 1,540.00  |
| Net single without Packaging | 1               | 0.33           | 5.00          | 14.00         | 22.00          | 0.00      |

#### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.



### EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH Auf dem Schüffel 3 Lüdenscheid, Germany https://www.assmann.com info@assmann.com