

DIGITUS Cat.5e U/UTP installation cable, 100 m, simplex, Eca

DK-1511-V-1-1
 EAN 4016032363804



CAT 5e U-UTP installation cable, 100 MHz Eca (PVC), AWG 24/1, 100 m paper box, sx, grey

The Digitus Cat 5e U/UTP installation cable is designed for use in the structured data center and the building cabling according to ISO/IEC 11801, DIN EN 50288-2-1, DIN EN 50173. The cable is perfectly suitable for the transmission of both analog and digital data and also supports POE. The shielding structure is composed of single shielded pairs with a tinned copper braid, which ensures excellent shielding and electrical values.

- Physical properties:
- Conductor: Bare annealed copper, solid AWG 24/1
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: Blue-white, orange-white, green-white, brown-white
- Individual pair shielding: None
- Overall shielding: None
- Outer sheath: Eca acc. to EN 50575; PVC
- Outer sheath diameter (nominal): 0.50 mm nominal
- Outer sheath color: Grey (RAL 7035)
- Mechanical properties:
- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +75 °C

- Operating temperature range: -20 °C up to +60 °C
- Installation temperature range: 0 °C up to +50 °C
- Overall diameter Simplex (nominal): 4.7 mm nominal
- Electrical properties:
- Impedance: 100±5 Ohm @ 1-600 MHz
- Capacitance: 40 pF/m nominal @ 800 Hz
- Capacitance unbalance (pair-ground): 1.5 pF/m max. @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC loop resistance: 147 Ohm/km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: CA-Type 3
- Signal propagation delay: 535 nS/100 m max.
- Propagation delay: 20 nS/100 m max.
- Separating class: „b“ acc. to EN 50174-2
- NVP: 69%
- Assortment: Twisted Pair Installation Cables
- Category: CAT 5e
- Shielding: U-UTP, unshielded
- CPR: Eca
- Length: 100 m
- Color: grey
- Jacket: PVC
- Structure: 4 x 2 AWG 24/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	2.60	12.00	23.00	24.00	6,624.00
Packaging Unit Inside	1	2.60	12.00	23.00	24.00	6,624.00
Packaging Unit Single	1	2.60	12.00	23.00	24.00	6,624.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:




DIGITUS

CPR-Symbole (CPR symbols) and **Leistungseigenschaften** (Performance characteristics) table.

Leistungseigenschaften	Leistungseigenschaften (MHz)	Leistungseigenschaften (MHz)
B2ca	1+	1+
Cca	3	3
Dca	3	3
Eca	3	3

Brand (Brand): Cca, s1a, d1, a1



Intertek ETL Verified Certificate of Conformance Number: 16112661CR10014

Intertek

ETL Verified Certificate of Conformance Number: 16112661CR10014

Technical Specifications:

- Model: DK-1511-V-1.1
- Material: PVC
- Color: Blue
- Length: 100m
- Category: CAT 5e
- Shielding: Unshielded
- Conductor: Bare Copper

DIGITUS

Leistungseigenschaften Transmitter Properties

MHz	ATT	MIT	PM MIT	ACN	PA-EN	PL	PK-EN	PS-EN
1	2	0.2	0.3	0.2	0.2	0.2	0.2	0.2
10	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
20	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
30	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
100	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
200	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1



DIGITUS

Produktinformation Product Information

Produktinformation	Physikalische Spezifikationen Physical Properties
Modellnummer: DK-1511-V-1.1	Farbe: Blau
Material: PVC	Material: PVC
Farbe: Blau	Material: PVC
Material: PVC	Material: PVC
Material: PVC	Material: PVC

Technische Eigenschaften Mechanical Properties

Technische Eigenschaften
Stärke: 1.0mm
Temperaturbereich: -20°C bis +60°C
Temperaturbereich: -20°C bis +60°C



DIGITUS

CAT 5e U/UTP Installation Cable, 100 m, Simplex, Eca

- 100 MHz
- 1 Gbit Ethernet
- AWG 24/1
- 20° / +60°
- Eca
- CPR class

