

DIGITUS Cabo de ligação Type-C™ USB

AK-300136-010-S
EAN 4016032368731



USB Type-C connection cable, type C to A M/M, 1.0m, 3A, 5GB, 3.0 Version, bl

Para a ligação de dispositivos finais USB externos (com conector fêmea C , p. ex., Tablet ou Smartphone) ao anfitrião USB (p. ex., computador portátil ou Hub USB). Taxa de transferência até 5 Gbps (Super Speed).

Para uma sincronização e carregamento super rápidos

- Transferência de dados de elevada velocidade até 5 Gbit/s - 10 vezes mais rápida do que USB 2.0
- Suporte fonte de alimentação até 3A
- Suporta a especificação USB PD (Power delivery).
- Compatibilidade reversa de USB 2.0 e 1.1
- Conector Type-C- utilizável dos dois lados

- Assortment: USB Cables
- AWG: 24/28
- Color cable: black
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB A, plug
- Connector surface: nickel-plated
- Ferrite filter: none
- Hoods: molded
- Packaging: Polybag
- USB compliance: USB 3.0 / 3.1
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

Attributes

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	150	10.90	50.00	32.00	21.00	33,600.00
Packaging Unit Inside	10	0.73	30.00	20.00	3.70	2,220.00
Packaging Unit Single	1	0.07	9.00	9.00	1.50	121.50
Net single without Packaging	1	0.05	9.00	9.00	1.50	0.00

More images:





Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com