

# DIGITUS Módulo compatível com HP mini GBIC (SFP), 1,25 Gbps, 0,55 km

DN-81000-01  
EAN 4016032369936



### 1.25 Gbps SFP Module, Multimode, HP-compatible LC Duplex Connector, 850nm, up to 550m, HP Aruba

O módulo transceptor DIGITUS® Mini GBIC (SFP) proporciona alta qualidade e fiabilidade. Quer seja a partir de interruptor para interruptor, conversor para interruptor, conversor para conversor ou qualquer outra aplicação: a vasta gama de módulos DIGITUS® permite a utilização flexível da tecnologia de fibra ótica. A conformidade com a norma MSA (Multi Source Agreement) garante a compatibilidade com fabricantes terceiros.

#### A ligação de fibra ótica Plug and Play

- Compatível com HP
- Compatível com HP-Aruba
- Módulo Mini GBIC SFP (Small Form Factor Pluggable)
- Alta qualidade e excelente proteção contra falhas
- Velocidade de dados máxima de 1,25 Gbps
- Está em conformidade com a norma IEEE 802.3z Gigabit
- Produto laser de classe 1 em conformidade com a EN 60825-1
- Instalação Plug and Play simples
- Compatível com a norma MSA (Multi Source Agreement)
- Hot pluggable
- Ligação: 1x LC Duplex

- 1000Base-SX - para distâncias curtas
- Comprimento de onda: 850nm
- Potência de transmissão: Mínima -8 dBm, máxima -3 dBm
- Sensibilidade de receção: mínima -20 dBm
- Para uma distância até 0,55 km
- Adequado para cabos de fibra ótica multimodo de 50/125 µm e 62,5/125 µm
- Mecanismo de bloqueio seguro e rápido
- Temperatura de funcionamento: 0°C-70°C

#### Attributes

- Mode: Multimode
- Connector: LC
- Distance (km): 0.5
- Wavelength: 850 nm
- DDM Support: no
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: HP, Universal (MSA)
- Ethernet speed: Gigabit

#### Package contents

- Módulo SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	240	8.50	50.00	29.00	54.50	79,025.00
Packaging Unit Inside	30	1.06	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.04	3.10	11.80	9.00	329.22
Net single without Packaging	1	0.02	1.00	5.90	0.80	0.00

#### Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.

- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)