


DIGITUS Cat.7A S/FTP, installation cable, 500 m, duplex, Dca-s1a d1 a1

DK-1743-A-VH-D-5
EAN 4016032380610



CAT 7A S-FTP installation cable, 1500 MHz Dca (EN 50575), AWG 22/1, 500 m drum, dx, yellow

The Digitus Cat 7 installation cable is designed for use in the structured data center and the building cabling according to ISO/IEC 11801, DIN EN 50288-4-1, DIN EN 50173, IEC 61156-7, EN 50288-9-1. The cable is perfectly suitable for the transmission of both analog and digital data and also supports POE and POE+. The shielding structure is composed of single shielded pairs with a tinned copper braid, which ensures excellent shielding and electrical values.

Future-oriented standards and high-end quality for your network.



- Physical properties:
- Basic conductor: Solid AWG 22/1, bare annealed copper, diameter 0.62 mm nominal
- System/s of AVCP: AVCP 3
- Insulation: SFS-PE (Foam-Skin Polyethylene)
- Total number of insulated conductors: 8, twisted in 4 pairs
- Color code: blue-white, orange-white, green-white, brown-white
- Individual pair shielding: Aluminum foil, providing 100 % coverage
- Overall shielding: Copper wire braid
- Outer jacket: Halogen-free (FRNC-C/LSZH-3)
- Outer jacket diameter: 0.6 mm nominal
- Color: Yellow (RAL 1016)
- Length: 500 m
- Mechanical properties:
- Tensile loading: 150N max.
- Dynamic bending radius: 8x AD mm min.
- Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +60 °C
- Operating temperature range: -20 °C up to +60 °C

- Temperature installation range: 0°C to +50°C
- Overall diameter: 8.0 mm nominal
- Flame retardancy: IEC 60332-3-24
- Halogen-free & smoke-proof: IEC 60754-2 & IEC 61034
- Fire load: 700 MJ/km
- Weight: 70 kg/km
- Electrical properties:
- Mean impedance: 100±5 Ohm @ 1-600 MHz
- Capacitance: 40 pF/m nominal @ 1 KHz
- Capacitance unbalance (pair-ground): 1.6 pF/m max. @ 1 KHz
- Insulation resistance: 5 GOhm x km min.
- DC loop resistance: 147 Ohm/Km max. (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: Grade 1 (CA-Type 1b)
- Propagation delay: 10 nS/100 m max.
- Signal propagation delay: 450 nS/100 m max.
- Separating class: "d" acc. to EN 50174-2
- NVP: 75%
- Flame spread: EN 60332-1-2 (LSOH-PVC)
- Halogen-free, corrosiveness: EN 60754-1/2 (LSOH)
- Smoke density: EN 61034-2
- Assortment: Twisted Pair Installation Cables
- Category: CAT 7A
- Shielding: S-FTP, pairs in metal foil and braid shielding
- CPR: Dca
- Length: 500 m
- Color: yellow
- Jacket: LSOH
- Structure: 4 x 2 AWG 22/1, solid twisted pair


Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	1	71.00	50.00	53.00	53.00	140,450.00
Packaging Unit Inside	1	71.00	50.00	53.00	53.00	140,450.00
Packaging Unit Single	1	71.00	50.00	53.00	53.00	140,450.00
Net single without Packaging	1	71.00	0.00	0.00	0.00	0.00

More images:

DIGITUS	
Produktbeschreibung / Product Information	Physikalische Spezifikationen / Physical Properties
<p>Technische Beschreibung / Technical Description</p> <p>Hersteller: DIGITUS Professional Network</p> <p>Modellnummer: DK-1743-A-VH-D-5</p> <p>Material: PVC, PE, LSZH</p> <p>Farbe: Gelb</p> <p>Abmessungen: 500m Länge</p>	<p>Technische Spezifikationen / Technical Specifications</p> <p>Standard: EN 50323-3-10, EN 50323-3-11</p> <p>Kategorie: CAT 7 S/FTP</p> <p>Paarung: 2x2 (Duplex)</p> <p>Übertragungsfrequenz: bis 600 MHz</p> <p>Impedanz: 100 Ohm</p> <p>Temperaturbereich: -20°C bis +70°C</p> <p>Flammverhalten: LSZH</p>



GHMT	
Certificate	Zertifikat
<p>Class E</p> <p>GHMT logo</p>	<p>Class E</p> <p>GHMT logo</p>



EN Normen	Bezeichnung	Leistungsleistung (dB/100m)	Anzahl der verdrillten Leiter	Zusammenfassung
B2ca	Sehr hoch	1+	4	S
Cca	Hoch	1	4	S
Dca	Mittel	3	4	d
Eca	Gering	3	4	a

CAT 7a S/FTP Installation Cable, 500m, Duplex, Dca

PAIRS	UTP	STP	PL SHIELD	ALU	PL ALU SH	AL	SHIELD	PL SHIELD
1	14	16	18	20	22	24	26	28
2	14	16	18	20	22	24	26	28
3	14	16	18	20	22	24	26	28
4	14	16	18	20	22	24	26	28
5	14	16	18	20	22	24	26	28
6	14	16	18	20	22	24	26	28
7	14	16	18	20	22	24	26	28
8	14	16	18	20	22	24	26	28

