

# DIGITUS Wall Mounting Cabinets - Slim

**DN-19 WM-V4U-SL**  
**EAN 4016032383253**



**Wall mounting cabinet, slim 800x640x220 mm, 4U vertical, color grey (RAL 7035)**

The 483 mm (19") Wall Mounting Cabinet of the Sim Series allows a vertical mounting of 4U in depth. Especially space saving for networks, DVR, sound equipment, paging- and patching applications or other 483 mm (19") active components.

**Slim design with mounting profiles for vertical installations inside**

- 1.0 - 1.5 mm strong steel sheet
- 483 mm (19") mounting areas inside: 4U in depth
- Punched out cable entries with plastic cover on all sides (145x70 mm)
- Bottom is prepared for fan units
- Lockable front door with air ventilation slots
- Door stop is easy to change
- Packaging dimensions (HxWxD): 820x660x230 mm

- Max. equipment mounting height inside: 610 mm
- Cabinet type: Wall mounting cabinet, home automation
- Color: light grey, RAL 7035
- Depth: 220 mm
- Front door: Steel door, closed, single opening
- Load capacity: 100 kg
- Side panels: Both sides
- Units: 4
- Width: 640 mm
- IP protection class: IP20
- Mounted: yes

**Package contents**

- Earthing wire set
- 2 x Keys

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	18.00	23.00	66.00	82.00	124,476.00
Packaging Unit Inside	1	18.00	23.00	66.00	82.00	124,476.00
Packaging Unit Single	1	18.00	23.00	66.00	82.00	124,476.00
Net single without Packaging	1	16.00	22.00	64.00	80.00	0.00

**More images:**



**Safety notes**

- Ensure adequate ventilation to prevent the installed devices from overheating.
- Network cabinets should not be overfilled and the ventilation openings must not be blocked.
- Cables should be laid neatly and organized in cable ducts or trays.
- Use surge protection devices to protect sensitive devices from power surges or lightning strikes.
- Avoid moisture or wetness while observing the respective IP protection class.
- Ensure that the cabinet and the devices used are properly earthed.
- In regions with frequent thunderstorm activity, professional lightning protection should be integrated into the power supply.
- To avoid uneven loading, always mount the heaviest units at the bottom of the cabinet.
- Disconnect the installed devices from the power supply during maintenance or installation work.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)