

# DIGITUS USB Type-C Connection Cable

**DB-300138-010-S**  
**EAN 4016032383819**



**USB Type-C connection cable, type C to C M/M, 1.0m, 5V/3A 15W, 480MB, 2.0, b1**

For connection of external USB devices (with C socket, e. g. PC, Tablet or Smartphone) to the USB Host (e. g. PC, Notebook). Datatransferrate up to 480 Mbps (High-Speed).

**For superfast synchronising and charging**

- High speed USB data transfer rate up to 480 Mbps
- Supports up to 5V/3A 15W, 480Mbps Power supply
- Support of USB PD (Power Delivery) specification
- Type-C connector can be used in both directions
- Assortment: USB Cables

- AWG: 24/28
- Color cable: black
- Color connector: black
- Connector 1: USB C, plug
- Connector 2: USB C, plug
- Connector surface: nickel-plated
- Hoods: molded
- Wire material: CU
- Length: 1 m
- Shielding: Double shielding
- USB-C Products: yes

| Logistics                    |              |             |            |            |             |                 |
|------------------------------|--------------|-------------|------------|------------|-------------|-----------------|
|                              | Number (pcs) | Weight (kg) | Depth (cm) | Width (cm) | Height (cm) | cm <sup>3</sup> |
| Packaging Unit Carton        | 100          | 13.13       | 18.00      | 24.00      | 31.00       | 13,392.00       |
| Packaging Unit Inside        | 50           | 6.56        | 16.00      | 11.00      | 29.00       | 5,104.00        |
| Packaging Unit Single        | 1            | 0.13        | 3.00       | 5.50       | 10.00       | 165.00          |
| Net single without Packaging | 1            | 0.10        | 9.00       | 9.00       | 0.60        | 0.00            |

**More images:**



**Safety notes**

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)