

DIGITUS Módulo 1,25 Gbps SFP cobre, RJ45

DN-81005
EAN 4016032389484



1.25 Gbps Copper SFP Module, RJ45 10/100/1000Base-T, up to 100m

O módulo transceptor DIGITUS® Mini GBIC (SFP) proporciona alta qualidade e fiabilidade. O módulo oferece a possibilidade ideal de expandir o seu comutador de rede Gigabit com uma porta Uplink SFP livre para uma ligação RJ45 adicional. Graças à capacidade Hot-Plug, o utilizador pode instalar o módulo sem interromper o tráfego de rede, nem necessitar de reiniciar o dispositivo. A conformidade com a norma MSA (Multi Source Agreement) também garante a compatibilidade com os fabricantes de comutadores de rede mais comuns.

A extensão Plug and Play para o seu comutador de rede

- Módulo Mini GBIC SFP (Small Form Factor Pluggable)
- Compatível os seguintes fabricantes: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Taxa de dados máxima bidirecional até 1,25 Gbps

- Está em conformidade com a norma IEEE 802.3z Gigabit
- Alta qualidade e excelente proteção contra falhas
- Instalação Plug and Play simples
- Compatível com a norma MSA (Multi Source Agreement)
- Hot pluggable - é possível instalar durante o funcionamento
- Ligação: 1x RJ45, CAT 5
- Distância: até 100 m
- Temperatura de funcionamento: 0°C~70°C
- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- Módulo SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.02	1.50	1.50	7.00	0.00

More images:



Product Number	EMC Code	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Version
Full Duplex							
Dsh-0001	AS100020000	10 Gbit/s	2 km	LC Multimode Duplex	10 Gbit/s	0 to +70 °C	
Dsh-0002	AS100020010	10 Gbit/s	2 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	
Dsh-0004	AS100020012	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	
Single							
Dsh-0005	AS100020001	10 Gbit/s	20 km	LC Multimode Duplex	10 Gbit/s	0 to +70 °C	
Dsh-0006	AS100020002	10 Gbit/s	20 km	LC Singlemode Duplex	10 Gbit/s	0 to +70 °C	
Dsh-0007	AS100020003	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	
Dsh-0008	AS100020004	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	
Dsh-0009	AS100020005	10 Gbit/s	80 km	LC Singlemode Duplex	10 Gbit/s	0 to +70 °C	
Dsh-0010	AS100020006	10 Gbit/s	80 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	
SM							
Dsh-0011	AS100020011	10 Gbit/s	20 km	LC Multimode Duplex	10 Gbit/s	0 to +70 °C	
Dsh-0012	AS100020012	10 Gbit/s	20 km	LC Singlemode Duplex	10 Gbit/s	0 to +70 °C	
Dsh-0013	AS100020013	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	✓
Dsh-0014	AS100020014	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	✓
Dsh-0015	AS100020015	10 Gbit/s	20 km	LC Singlemode Duplex	10 Gbit/s	0 to +70 °C	✓
Dsh-0016	AS100020016	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	✓
Dsh-0017	AS100020017	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	✓
Dsh-0018	AS100020018	10 Gbit/s	20 km	LC Singlemode Duplex	10 Gbit/s	0 to +70 °C	✓
Dsh-0019	AS100020019	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	✓
Dsh-0020	AS100020020	10 Gbit/s	20 km	LC Singlemode Duplex	7.5 Gbit/s @ 10 Gbit/s	0 to +70 °C	✓

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.
 ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com