

DIGITUS Módulo 1,25 Gbps SFP cobre, RJ45

DN-81005
EAN 4016032389484



1.25 Gbps Copper SFP Module, RJ45 10/100/1000Base-T, up to 100m

O módulo transceptor DIGITUS® Mini GBIC (SFP) proporciona alta qualidade e fiabilidade. O módulo oferece a possibilidade ideal de expandir o seu computador de rede Gigabit com uma porta Uplink SFP livre para uma ligação RJ45 adicional. Graças à capacidade Hot-Plug, o utilizador pode instalar o módulo sem interromper o tráfego de rede, nem necessitar de reiniciar o dispositivo. A conformidade com a norma MSA (Multi Source Agreement) também garante a compatibilidade com os fabricantes de computadores de rede mais comuns.

A extensão Plug and Play para o seu computador de rede

- Módulo Mini GBIC SFP (Small Form Factor Pluggable)
- Compatível os seguintes fabricantes: Allied Telesis, Allnet, Avaya, CISCO, D-Link, Edimax, FINISAR, FORCE 10, Gigamon Intellinet, KTI Networks, Level One, PLANET, Tenda, TP-Link, TRENDnet, Mikrotik, ENTERASYS, RIVERSTONE, Unifi, Ubiquiti, ZyXEL, ZTE
- Taxa de dados máxima bidirecional até 1,25 Gbps

- Está em conformidade com a norma IEEE 802.3z Gigabit
- Alta qualidade e excelente proteção contra falhas
- Instalação Plug and Play simples
- Compatível com a norma MSA (Multi Source Agreement)
- Hot pluggable - é possível instalar durante o funcionamento
- Ligação: 1x RJ45, CAT 5
- Distância: até 100 m
- Temperatura de funcionamento: 0°C-70°C

Attributes

- Mode: Copper
- Connector: RJ45
- Distance (km): 0.1
- DDM Support: no
- Manufacturer compatibility: Universal (MSA)
- Ethernet speed: Gigabit

Package contents

- Módulo SFP

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	120	7.00	25.40	39.40	55.00	55,041.80
Packaging Unit Inside	30	1.75	7.00	20.00	30.00	4,200.00
Packaging Unit Single	1	0.06	3.20	9.30	12.00	357.12
Net single without Packaging	1	0.02	1.50	1.50	7.00	0.00

More images:



Product Number	MM Code	Speed	Distance	Connector	Mounting	Operating Temperature	Industrial Version
DM-0101	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0102	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0103	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0104	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0105	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0106	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0107	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0108	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0109	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0110	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0111	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0112	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0113	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0114	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0115	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0116	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0117	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0118	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0119	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓
DM-0120	42700000000	1.0 Gbps	2 km	LC Multimode Duplex	190mm	0 to +70 °C	✓

Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com