

DIGITUS Conversor de média PoE Gigabit, RJ45 / SC, MM, PSE

DN-82150
EAN 4016032390022



Gigabit Ethernet PoE+ Media Converter, Multimode 802.3af, 30W, SC connector, up to 0.5km

Os conversores de média da DIGITUS® consistem na solução ideal para a migração de sinais de fibra de vidro. A partir de agora, é possível aceder à tecnologia de fibra e transferir os sinais de rede ao longo de vários quilómetros sem ter de substituir toda a infra-estrutura de rede. A nossa grande variedade de produtos corresponde às suas necessidades individuais. O funcionamento intuitivo garante uma instalação fácil e rápida. Os anos de experiência e a grande variedade de produtos permitem que a DIGITUS® se torne num parceiro fiável para a sua engenharia de rede.

A solução de conversão ideal para transmissão de dados óticos

- Fonte de alimentação PoE, PSE
- Compatível com os padrões IEEE802.3af e IEEE802.3at
- Alimentação elétrica PoE via PIN 4/5 (V-) e PIN 7/8 (V+)
- Saída máxima total de 30 watt
- Compatível com as normas IEEE802.3, IEEE802.3u e IEEE802.3z
- Reconhecimento automático de cabos - função automática MDI/MDI-X
- Autorreconhecimento de full e half duplex
- Converte sinais de rede baseados em cabo em sinais de fibra ótica
- 10/100/1000Base-TX para 1000Base-SX
- Portas: 1x RJ45, 1x SC Duplex

- Alcance até 0,5km
- Comprimento de onda: 850nm
- Fibra dupla de modo múltiplo
- LED de diagnóstico sobre o estado e monitorização de atividade
- Fonte de alimentação: 48-52V DC
- Temperatura de funcionamento: -20°C - 65°C
- Temperatura de acondicionamento: -40°C - 85°C
- Dimensões (mm): 95 (C) x 71 (L) x 26 (A)
- MTBF: 500,000 horas

Attributes

- Connector 1: RJ45
- Connector 2: SC
- Mode: Multimode
- Distance (km): 0.5
- Industrial usage: no
- Broadcasting Mode: Unidirectional
- PoE injector: yes
- Ethernet speed: Gigabit

Package contents

- Conversor de média PoE Gigabit, RJ45 / SC, MM, PSE
- Peso: 20 g
- Fonte de alimentação

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	10	8.00	57.00	41.00	28.00	65,436.00
Packaging Unit Inside	1	0.80	24.00	13.00	6.00	1,872.00
Packaging Unit Single	1	0.80	24.00	13.00	6.00	1,872.00
Net single without Packaging	1	0.50	10.00	7.00	2.00	0.00

More images:



Safety notes

- Avoid direct contact with light sources: Fiber optic cables, especially those with active light sources such as lasers (e.g. in optical communication systems), can emit dangerous radiation that can damage eyes. Take care never to look directly into the light of an optical fiber, even if the light source is invisible to the naked eye.
- When working with fiber optic cables, especially during tests or when working with lasers, protective goggles should always be worn to protect against harmful radiation.
- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Do not kink or crush: Fiber optic cables are sensitive to mechanical stress.
- To protect cables from physical damage, they should be laid in special ducts or with protective materials
- Keep cable connectors clean: Fiber optic cables are sensitive to dust and dirt. Even small particles on the connectors can severely impair the signal quality.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
 Auf dem Schüffel 3
 Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com