

# DIGITUS DIGITUS CAT 6A U-FTP монтажный кабель витая пара

DK-1623-A-P-1  
EAN 4016032425991



## CAT 6A U-FTP patch cable, raw length 100 m, paper box, AWG 27/7, LSZH, sx, grey

Подходит для установки кабельных линий класса D, 100 МГц

### Отличная производительность и качество связи для Вашей сети.

- Изоляция: полиэтилен высокой плотности
- Основной проводник: многожильный AWG 26/7
- Изоляция: PE
- Общее количество изолированных проводников: 8, свиты в 4 пары
- Цветовой код: сине-белый, оранжево-белый, зелено-белый, коричнево-белый
- Индивидуальная экранировка пар: отсутствует
- Общее экранирование: отсутствует
- Диапазон рабочей температуры: -10 °C до +60 °C

- Цвет: Серый (RAL 7035)
- Механические свойства
- Растяжение: 150 Н макс.
- Сопротивление петли по пост. току: 147 Ом/км макс. (2% макс. разбаланс сопротивлений)

### Attributes

- Assortment: Twisted Pair Patch Cables
- Category: CAT 6A
- Shielding: U-FTP, pairs in metal foil
- Length: 100 m
- Color: grey
- Jacket: LSOH
- Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	4	11.50	42.00	31.00	31.00	40,362.00
Packaging Unit Inside	1	2.88	29.00	29.00	10.00	8,410.00
Packaging Unit Single	1	2.88	29.00	29.00	10.00	8,410.00
Net single without Packaging	1	2.60	10,000.00	5.80	5.80	0.00

### Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.
- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

**EU responsible person**

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH  
Auf dem Schüffel 3  
Lüdenscheid, Germany  
<https://www.assmann.com>  
[info@assmann.com](mailto:info@assmann.com)