

DIGITUS CAT 6A U/FTP twisted pair patch cord, raw

DK-1623-A-P-305
EAN 4016032426004



CAT 6A U-FTP patch cable, raw length 305 m, paper box, AWG 27/7, LSZH, sx, grey

The raw patch cords are manufactured and tested acc. to the ISO/IEC 11801 and DIN EN 50173 specifications. They will guarantee that the installed cabling system is compliant with the ISO & EN channel specification requirements and therefore provide optimum performance levels for your cabling. The raw patch cords are suitable for the direct assembly of RJ45 connector in order to produce patch cords.

Future-oriented standards and high-end quality for your network.

- Insulation: HD-PE
- Outer sheath diameter: 0.55 mm nominal
- Overall diameter: 5.8 mm nominal
- Tensile loading: 150 N max.
- Static bending radius: 4x AD mm min.
- Dynamic bending radius: 8x AD mm min.
- Shipping- and storage temperature range: -10 °C up to +75 °C
- Operating temperature range: -10 °C up to +60 °C
- Installation temperature range: 0 °C up to +50 °C
- DC loop resistance: $\leq 280 \Omega \text{ km}$
- Resistance unbalance $\leq 2\%$
- Insulation resistance: $\geq 2000 \text{ M}\Omega/\text{km}$ @500V
- Capacitance: nom. 48 nF/km @ 800 Hz
- Capacitance unbalance (pair-ground): $\leq 1500 \text{ nF/km}$

- Characteristic Impedance: $100 \pm 15 \Omega$ @ 10-100 MHz
- NVP: 67%
- Propagation delay: nom. $\leq 555 \text{ ns}/100 \text{ m}$
- Delay skew: nom. $\leq 50 \text{ ns}/100 \text{ m}$
- Test voltage (DC 1 min) core/core: 1000V
- Coupling attenuation: $\geq 40 \text{ dB}$
- Capacitance: 48 pF/m nominal @ 800 Hz
- Capacitance unbalance (pair-ground): 1.5 pF/m max. @ 1 KHz
- Insulation resistance: $2 \text{ G}\Omega \times \text{km min.}$
- DC loop resistance: 147 $\Omega/\text{km max.}$ (2% max. resistance unbalance)
- Voltage resistance: 72 Vdc max.
- Coupling attenuation: 40 dB
- Signal propagation delay: 450 ns/100 m max.
- Propagation delay: 20 ns/100 m max.

Attributes

- Assortment: Twisted Pair Patch Cables
- Category: CAT 6A
- Shielding: U-FTP, pairs in metal foil
- Length: 305 m
- Color: grey
- Jacket: LSOH
- Slim Version: no
- Structure: 4 x 2 AWG 27/7, twisted pair
- Flat Version: no

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	2	18.50	42.50	45.00	45.00	86,062.50
Packaging Unit Inside	1	9.25	39.00	39.00	20.00	30,420.00
Packaging Unit Single	1	9.25	39.00	39.00	20.00	30,420.00
Net single without Packaging	1	8.00	30,500.00	5.80	5.80	0.00

Safety notes

- When plugging and unplugging the cable, only grasp the plug and do not pull directly on the cable.
- Cables must not be kinked sharply or bent at tight angles, as this can damage the inner wires and lead to failures.
- Make sure that the cables are not under tensile load, as this can damage the insulation and the wires inside the cable.
- Ensure that cables are not laid in areas where they can be easily damaged mechanically.

- Cables should not be used in environments with extremely high or very low temperatures. Observe the product information on the maximum operating temperature of the cable
- Check cables regularly for visible damage such as cracks, kinks or signs of wear. Defective cables should be replaced immediately to avoid failures, short circuits or even electric shocks.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheid, Germany
<https://www.assmann.com>
info@assmann.com